


Dimension



Contact your Hyundai dealer for more information. The machine shown may vary according to International standards.
All US measurement rounded off to nearest pounds or inches.

HYUNDAI | FORKLIFT HEAVY INDUSTRIES CO.,LTD.

Head Office(Sales Office)
1 JEONHA-DONG, DONG-GU, ULSAN, KOREA Tel (82) (52) 202-7970, 7729 Fax (82) (52) 202-7979, 7720

U.S. Operation : Hyundai Construction Equipment U.S.A., Inc.
955 ESTES AVENUE, ELK GROVE VILLAGE IL, 60007 Tel (1) 847-437-3333 Fax (1) 847-437-3574

European Operation : Hyundai Heavy Industries Europe N.V.
VOSSENDAAL 11, 2440 GEEL, BELGIUM Tel (32) 14-562200 Fax (32) 14-593405-06

India Operation : Hyundai Construction Equipment India Private Limited
303, 3rd Floor, Siddhivinayak Aaurum, 33/1/1/2 Vadgaon Sheri,
Viman Nagar, Pune 411 014 India Tel 91-20-4003-8160 Fax 91-20-4003-8163

Specification

Identification				
1.1	Manufacturer	Hyundai	Hyundai	Hyundai
1.2	Manufacturer's type designation	15D-7E	18D-7E	20DA-7E
1.3	Drive: electric (battery or mains),diesel,petrol,fuel gas,manual	DIESEL	DIESEL	DIESEL
1.4	Type of operation:hand,pedestrian,standing,seated,order-picker	seated	seated	seated
1.5	Load capacity / rated load	kg	1,500	1,750
1.6	Load center distance	c mm	500	500
1.8	Load distance, center of drive axle to fork	x mm	394	399
1.9	Wheelbase	y mm	1,422	1,422
Weights				
2.1	Service weight	kg	2,850	3,020
2.2	Axle loading, loaded front/rear	kg	3,754 / 596	4,116 / 654
2.3	Axle loading, unloaded front/rear	kg	1,305 / 1,546	1,256 / 1,763
Wheels, Chassis				
3.1	Tires:solid rubber, superelastic, pneumatic, polyurethane	pneumatic	pneumatic	pneumatic
3.2	Tires size, front(φ x width)	6.50-10-12PR	6.50-10-12PR	6.50-10-12PR
3.3	Tires size, rear(φ x width)	5.00-8-10PR	5.00-8-10PR	5.00-8-10PR
3.5	Wheels, number front x rear (x=driven wheels)	x2 / 2	x2 / 2	x2 / 2
3.6	Track width, front	mm	889	889
3.7	Track width, rear	mm	914	914
Basic Dimensions				
4.1	Mast / fork carriage tilt forward / backward (α/β)	degrees	6 / 10	6 / 10
4.2	Lowered mast height	h1 mm	2,159	2,159
4.3	Free lift	h2 mm	145	150
4.4	Lift height	h3 mm	3,327	3,327
4.5	Extended mast height	h4 mm	4,343	4,343
4.7	Overhead load guard (cab) height	h5 mm	2,108	2,108
4.8	Seat height / standing height	h7 mm	1,049	1,049
4.12	Coupling height	h10 mm	262	257
4.19	Overall length	l1 mm	3,124	3,175
4.20	Length to face of forks	l2 mm	2,235	2,311
4.21	Overall width	b1 mm	1,067	1,067
4.22	Fork dimensions(hook type)	s / e / l mm	900 x 100 x 35	900 x 100 x 35
4.23	Fork carriage ISO 2328, class / type A,B		2A	3A
4.24	Fork-carriage width	b12 mm	980	980
4.31	Ground clearance, loaded, under mast	m1 mm	119	119
4.32	Ground clearance, centre of wheelbase	m2 mm	145	145
4.33	Aisle width for pallets 1,000x1,200 crossways (LxW)	Ast mm	3,579	3,607
4.34	Aisle width for pallets 800x1,200 lengthways (WxL)	Ast mm	3,780	3,808
4.35	Turning radius	Wa mm	1,984	2,014
4.36	Smallest pivot point distance	b13 mm	587	587
Performance Data				
5.1	Travel speed, unloaded	km/h	19.5	19.5
5.2	Lift speed, loaded/ unloaded	mm/sec	620 / 650	610 / 650
5.3	Lowering speed, loaded/unloaded	mm/sec	498 / 452	498 / 452
5.5	Drawbar pull, loaded	kg	1,669	1,679
5.7	Gradient performance, loaded/ unloaded	%	31.5 / 24.3	28.2 / 22.0
5.9	Acceleration time, loaded/ unloaded(10m)	sec	NA	NA
5.10	Service brake		FOOT	FOOT
Engine				
6.1	Engine manufacturer / type		KUBOTA V2203	KUBOTA V2203
6.2	Engine power acc. to ISO 1585	kw	30.8	30.8
6.3	Rated speed	1/min	2,400	2,400
6.4	No. of cylinder / cubic capacity	anz/cm³	4 / 2,197	4 / 2,197
6.5	Fuel consumption acc. To VDI cycle	ℓ / h	NA	2.86
Other Details				
8.1	Type of drive control		power shift	power shift
8.2	Operating pressure (MAIN / SECONDARY)	bar	195 / 155	195 / 155
8.3	Oil volume (Hydraulic)	ℓ	30	30
8.4	Sound level at driver's ear according to (DIN 12 053)	db(A)	80	80

1)with DZ mast +25mm;with integrated sideshift x=375mm(with DZ mast +25mm);with hook-on sideshift x=410.5mm(with DZ mast +25mm)



■ Some of the photos may include optional equipment.

15D/18D/20DA-7E


FORKLIFT TRUCKS Environmentally - Friendly

PLEASE CONTACT

15D/18D/20DA -7E

New criterion of Forklift Trucks

Hyundai introduces a new line of 7E-series diesel forklift trucks.
Excellent power and performance makes your business more profitable.



OPSS (Operator Presence Sensing System)

Control of mast tilting, lifting and lowering is not possible through operation of the appropriate control when the operator is not in the normal position. (Option)



High Power & Performance

Powerful Engine

KUBOTA V2203 Engine

Market approved quality of Kubota V2203 engine ensures incomparable performance, durability and additional value to the machine. 30.8kW of the engine is more than enough to suit any work, not just with normal 30.8kW but with special attachments requiring high power as well.


(EPA / Tier-3 Certified)

30.8kW/2,300rpm



State-of-the-art hydraulic system

The latest large-capacity hydraulic system reacts quickly during operation, and a low-noise control valve increases both efficiency and durability.



The new master on the job-site!

Smooth running, efficient and ergonomically designed, 15D/18D/20DA-7E series are made to meet your needs.



■ Some of the photos may include optional equipment.



Fast and stable performance

Being able to quickly raise and lower the mast, as well as tilt it forward and backward, provides the best operational conditions during unloading. When the truck is fully loaded, mast lowering speed is carefully controlled to ensure safety by the down control valve.

Faster travel speed & gradeability


The powerful high-output engine provides greater acceleration, better gradeability and faster travel speed on any tough terrain or slope.

Gradeability(Loaded)

15D-7E	21.1°
18D-7E	19.1°
20DA-7E	17.9°


Travel speed(Unloaded)

15D-7E	19.3km/h
18D-7E	19.3km/h
20DA-7E	19.3km/h



Increased mast tilting angle

The mast tilting angle of 6 degrees forward and 10 degrees backward, the operator can safely and rapidly perform loading and unloading jobs.



Wet disc brake system

The wet disc brake system is virtually maintenance free and is enclosed to protect from dust and water.



Fully hydrostatic power steering

A hydraulic steering system always guarantees smooth and flexible steering, preventing overrun and kick-back.



Key-locking fuel cap

Increased security on job sites with locking fuel cap, plus an increased capacity fuel tank for less down time.

Comfortable Operation



Adjustable steering wheel

Steering wheel with horn button can be adjusted by a lever on the right-hand side for the most comfortable operator position.



Easy and safe shift lever

A single lever on the left side of the steering column gives the operator fast, easy control of direction.



Multi-function switch lever

Multi-functional switch lever gives easy access to lights and horn.



Quick response of operating control levers

Only minimal operator's effort is required for precise, safe and productive control.



Some of the photos may include optional equipment.


Ergonomically designed with the operator in mind!

A design based on human engineering relieves fatigue and increase operator's efficiency.



Ergonomically positioned pedals

Based on human engineering, the accelerator, brake and inching pedals are optimally positioned for convenience while operating the equipment.



Cup holder & console box

Additional storage spaces are located inside the operating space for operator's convenience.



New high visibility for safe operation

The operator is able to work with increased safety and accuracy due to a wider view mast.

Operator friendly gauges and water-resistant monitor panel



- | | |
|---------------------------------------------|---------------------------|
| ① Parking brake lamp | ⑨ Water separator lamp |
| ② Directional indicators | ⑩ Pre-heater indicator |
| ③ Fuel warning lamp | ⑪ Water temperature gauge |
| ④ Engine oil warning lamp | ⑫ Fuel gauge |
| ⑤ Transmission oil temperature warning lamp | ⑬ Hour meter |
| ⑥ Battery charging warning lamp | ⑭ Engine check lamp |
| ⑦ Air cleaner filter warning light | ⑮ Seat belt warning |
| ⑧ Working light indicator | ⑯ OPS warning |

Easily adjustable suspension seat

An attractive and adjustable seat, based on a human engineering design, provides great comfort, safety and durability.



Full floating overhead guard mount

The anti-vibration rubber is installed between the guard and truck frame to reduce the source of vibration and noise while driving. This not only reduces operator's fatigue but also increases safety.



Endurance & Safety


Strong overhead guard

The safety overhead guard exceeds EEC and ANSI regulations and protects the operator during hazardous jobs.



Parking brake

Ratchet type parking brake requires less efforts from the operator to set.



Highly durable split type drive axle


Powershift transmission provides fast travel speed and quiet travel under any heavy load condition, and boosts work efficiency.

Enhanced safety through high durability!

Safety and durability are priorities in the design of the equipment.



■ Some of the photos may include optional equipment.




Large footboard & hand grip

Wide "open" step offers convenience and safety when entering and exiting truck.


Heavy duty single unit frame

Heavy duty single unit type frame, designed on the basis of accurate structural analysis, guaranteeing durability and safety.



Easy access of electrical Components

Various electric parts are centralized in dash board resulting in improvement in maintenance




Expansion bellows

The expansion bellows absorbs vibration and reduces noise generated from the exhaust gas system and also extends the life cycle of exhaust gas system.



Bright, protected headlights

Bright, protected headlights is positioned for exceptional visibility.



Ground clearance

The engine and transmission are assembled horizontally and positioned high in the frame to protect expansive components during operation on rugged surface.

Durability Easy Maintenance



Electrically monitored air filter
Air cleaner sensor alerts the operator of a restricted air filter and allows replacement before damage.



Easy maintenance oil check
The T/M oil level can be checked easily without any disassembly.



Brake fluid reservoir
Highly visible, easily accessible reservoir makes for quicker daily inspections.



An accessible, compact fuse box for easy inspection



Centralized design for easy service!
An ideal arrangement of component parts ensures easy access and convenience for maintenance.




Easy change air cleaner
The air filter is readily accessible for cleaning or replacement. (7inch Cyclone Type)



Portable side cover



Rotational battery installation



Aluminum radiator with superb protection against heat



Quick and easy engine oil check

Mast Specification																			
Mast Type		Overall Height Lowered	Maximum Fork Height		Free Lift				Tilt Angle (deg)		Load Capacity w / o Side Shift (500 mm) LC Single Tire			Load Capacity w / Side Shift (500 mm) LC Single Tire			Truck Weight Unload Single Tire		
					With bkr		With / o bkr				15D-7E	18D-7E	20DA-7E	15D-7E	18D-7E	20DA-7E	15D-7E	18D-7E	20DA-7E
			15D/18D 20DA-7E	15/18D-7E	20DA-7E	15D/18D-7E	20DA-7E												
			mm	mm	mm	mm	mm	mm	mm	mm	Fwd	Bwd	kg	kg	kg	kg	kg	kg	kg
2-Stage Limited Free Lift	V250	1,755	2,525	2,530	145	150	145	150	6	10	1,500	1,750	2,000	1,400	1,650	1,890	2,798	2,916	3,063
	V270	1,855	2,725	2,730	145	150	145	150	6	10	1,500	1,750	2,000	1,400	1,650	1,890	2,812	2,930	3,076
	V300	2,005	3,025	3,030	145	150	145	150	6	10	1,500	1,750	2,000	1,400	1,650	1,890	2,832	2,950	3,096
	*V330	2,155	3,325	3,330	145	150	145	150	6	10	1,500	1,750	2,000	1,400	1,650	1,890	2,852	2,970	3,116
	V350	2,255	3,525	3,530	145	150	145	150	6	10	1,500	1,750	2,000	1,400	1,650	1,890	2,865	2,983	3,130
	V370	2,355	3,725	3,730	145	150	145	150	6	10	1,500	1,750	1,950	1,400	1,650	1,850	2,879	2,997	3,143
	V400	2,505	4,025	4,030	145	150	145	150	6	10	1,475	1,700	1,550	1,390	1,600	1,470	2,903	3,021	3,168
	V450	2,855	4,525	4,530	145	150	145	150	6	6	1,425	1,625	1,500	1,340	1,535	1,420	2,970	3,088	3,235
	V500	3,105	5,025	5,030	145	150	145	150	6	6	1,350	1,450	1,050	1,270	1,370	980	3,003	3,121	3,268
	V550	3,355	5,525	5,530	145	150	145	150	6	5	1,050	1,000	825	970	930	760	3,037	3,142	3,289
3-Stage Full Free Lift	TF370	1,805	3,735	3,740	798	803	1,299	1,300	6	6	1,500	1,725	1,900	1,400	1,650	1,810	2,895	3,065	3,221
	TF400	1,905	4,035	4,040	898	903	1,399	1,400	6	6	1,475	1,675	1,850	1,400	1,610	1,770	2,914	3,084	3,240
	TF430	2,005	4,335	4,340	998	1,003	1,499	1,500	6	6	1,425	1,625	1,800	1,365	1,560	1,720	2,933	3,103	3,259
	TF450	2,105	4,535	4,540	1,098	1,103	1,599	1,600	6	6	1,400	1,600	1,700	1,340	1,535	1,620	2,953	3,123	3,279
	TF470	2,155	4,735	4,740	1,148	1,153	1,649	1,650	6	6	1,375	1,475	1,400	1,315	1,415	1,350	2,964	3,134	3,290
	TF500	2,255	5,035	5,040	1,248	1,253	1,749	1,750	6	6	1,350	1,425	1,050	1,290	1,370	1,020	2,984	3,154	3,310
	TF550	2,455	5,535	5,540	1,448	1,453	1,949	1,950	6	5	1,125	1,125	800	1,075	1,085	780	3,022	3,192	3,348
	TF600	2,655	6,035	6,040	1,648	1,653	2,149	2,150	6	5	775	775	500	750	755	490	3,094	3,264	3,420
	TF650	2,855	6,535	6,540	1,848	1,853	2,349	2,350	3	3	525	525	450	510	510	440	3,138	3,308	3,464
	TF700	3,055	7,035	7,040	2,048	2,053	2,549	2,550	3	3	375	350	325	365	340	315	3,174	3,344	3,500

* Standard

